

FATEK FV SERIES OPERATOR TERMINAL



● Product specification

| | | |
|---|---|---|
| Model | FV035ST-C10 | |
| Size | 3.5" | |
| Display Type | Color STN LCD | |
| Resolution | 320 × 240 Pixels | |
| Contrast Adjustment | 16 adjustable by touch screen function | |
| Backlight | LED backlight | |
| Touch Screen | Type | Digital Resistor Membrane |
| | Resolution | 1024*1024 |
| Power Supply | 24VDC±10% Isolation ; Consumption 10W less | |
| CPU | RISC ARM 32Bit CPU | |
| System Memory | 2M Bytes | |
| System Working Memory | 512K Bytes) | |
| Battery Backup Memory | -- | |
| Communication Port | COM1/9pin : RS232/RS422/RS485 COM2/Terminal 4Pin : RS422/RS485 | |
| Expansion Interface Card | Not Support | |
| Web Comm. Port | Yes(N type) | |
| Panel Protection | IP65 / NEMA 4 | |
| Storage Temperature | -20°~ 60° | |
| E n v i r o n m e n t | Operation Temperature | 0°~ 50° |
| | Humidity | 10%~90%(non-dewing environment : 39°C below) |
| | | 10 to 55Hz (X, Y, Z direction 1GHz , 30 min. vibrating testing) |
| | EMI | Complies with FCC Part 15 Class B |
| | CE | Complies with EN50081-2 and EN50082-2 standards |
| | | NEMA4/IP65 |
| Certificate | CE 、FCC | |
| Measurement(WxHxD mm) | 119.0 x 99.0 x 42.0 | |
| Hole Size (W x H mm) | 109.5 x 89.5 | |
| Net Weight (K.G) | 0.26 KG | |
| Consumption | 3W | |

● Dimensions

